

Towable Magnetic Sweepers - Aardvark Series™



Aardvark Series Landfill and construction site sweeper

Fully enclosed with automatic
clean off system.

Bluestreakequipment
The world's best cleaning equipment

www.bluestreakequipment.com

Landfill and Construction Site Needs/Problems

Aardvark Solutions

<p style="text-align: center;">Durability Equipment needs to be durable.</p>	<ul style="list-style-type: none"> • Fully enclosed magnet keeps debris out and off of the magnet and protects the main unit from the elements. • Angled 12 gauge steel bash bar and UHMW skid bar protect magnet in rough ground. • Flat proof tires.
<p style="text-align: center;">Easy and safe to use To avoid injuries and accidents.</p>	<ul style="list-style-type: none"> • Automatic clean off with the push of a button. No lifting of bins or debris trays. • “Easy sweeping height adjustment of 1 1/2” to 6” using continuous adjustment top link. • Safety flags and “Magnetic Sweeper” signage ensure the unit is seen and safe to tow
<p style="text-align: center;">Professional Performance and Power Landfills and construction sites need pickup power to pickup debris through dirt.</p>	<ul style="list-style-type: none"> • Maximum lifting height of 12” using 2 1/2” nail and maximum operating speed of 15 mph/24kph. • Optional Debris Digging Rake accessory digs out partially embedded debris so the magnet can pick it up.

Aardvark Specifications

 **Aardvark Series**

See this product in action.

View a demo on line.

Visit us at www.bluestreakequipment.com

Product Name

Aardvark - Towable Magnetic Sweeper

Sweeping Width

96"

Height of Sweeper Magnetic Housing

4.5"

Face Depth of Sweeper Magnetic Housing

9"

Magnet Dimensions Inside Housing

3 1/2"H x 8"W x 94"L

Ground Clearance

1.5" to 6"

Total Product Weight

1056lbs

Coupler

2" Ball coupler with 6 coupler height adjustment settings - 13", 15", 17", 19", 21", 23"

Cleaning Method

Automatic remote control

Wheels

5 bolt 16.5" x 6.5" flat proof hub and spindle

Sweeping Height Adjustability

Continuous from 1 1/2" to 6"

Tongue Weight

260 lbs

Frame Construction

Steel

Housing Construction

1/8" Aluminum

Magnetic Surface Area (square inches)

752 sq. in

Maximum Lifting Height

(measures in 2 1/2" 8 penny nails)

12"

Wear Protection

Front steel bashbar

UHMW skid bar

Maintenance Requirements

Grease bearing buddies on wheels, grease pillow blocks, charge battery




The world's best cleaning equipment
Aardvark

1645 Hwy 3, Delhi,
Ontario, Canada N4B 2W6

Tel: 1-519-582-1386

Fax: 1-519-582-2579

email: sales@bluestreakequipment.com

web site: www.bluestreakequipment.com

*The manufacturer reserves the right to modify the product at any time, without prior notice.